

MINIMUM SPACE & MAXIMUM PERFORMANCE!

THE JDM SLIM 2 IS OUR SMART ALL-ROUNDER WITH ONLY VERY LITTLE SPACE ON YOUR COUNTER!

- 2 drink selection buttons + chilled water
- Bag-in-box concentrates are stored under /behind the machine (for use of large bags eg. 10 litre)
- Preselection Hot or CO₂ – OPTIONAL (model Hot & Cold or CO₂)
- 1 central drink exit with LED lighting (hygienic tempered glass tube)
- Automatic cleaning and increased hygiene through airtight seal of concentrates
- Fully electronic control of concentrate dosage and output quantities
- Reliable and made-to-last – premium materials, robust surfaces
- Ease of use – easy refilling, programming, service and cleaning
- Perfect mixing result through patented MidMix®-system
- Multilingual LCD-Info Display (except ECO model)
- Preparation for payment systems + accounting (except ECO model)
- Carafe switch for quick serving by service staff - OPTIONAL



Anti-vandalism buttons



Easy access to product labels and technics

Available in the following versions:

JDM SLIM 2 STILL, JDM SLIM 2 CO₂, JDM SLIM 2 ECO (with LED-bar instead of LCD display), JDM SLIM 2 Hot & Cold, JDM SLIM 2 Hot & Ambient

TECHNICAL DATA & PRICES

DATA	JDM SLIM 2 ECO	JDM SLIM 2 STILL	JDM SLIM 2 CO2	JDM SLIM 2 Hot & Cold	JDM SLIM 2 Hot & Ambient
Price in € excl. VAT	€	€	€	€	€
Art. Nr.	frucB0240	frucB0241	frucB0242	frucB0243	frucA0247
Width	260 mm	260 mm	260 mm	260 mm	260 mm
Height	360 mm	360 mm	360 mm	360 mm	360 mm
Depth	420 mm	420 mm	420 mm	420 mm	420 mm
Exit height	160 mm	160 mm	160 mm	160 mm	160 mm
Weight	25 kg	25 kg	29 kg	27 kg	13 kg
Preselections	0	1	1	1	1
Product selection buttons (incl. water)	3	3	3	3	3
ESI product labels ²	✓	✓	✓	✓	✓
Flavours	2	2	2	2	2
Mixing ratio concentrates	1+4 ...1+49*	1+4 ...1+49	1+4 ...1+49	1+4 ...1+49	1+4 ...1+49
Concentrates in machine	0	0	0	0	0
Dosage of product selection	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS
Cooling capacity	19 l/h	19 l/h	19 l/h	19 l/h	19 l/h
Dispensing temperature	5°C - ambient	5°C - ambient	5°C - ambient	5°C - 75°C	Ambient - 75°C
Water pressure in bar	min 1,5 - max 6	min 1,5 - max 6	min 1,5 - max 6	min 1,5 - max 6	min 1,5 - max 6
Voltage	230 V/ 50 Hz	230 V/ 500 Hz	230 V/ 50 Hz	230 V/ 50 Hz	230 V/ 50 Hz
Power max.	250 W	250 W	320 W	2.700 W	2.400 W
with CO2-carbonator	-	-	✓	-	-
FSS ¹	✓	✓	✓	✓	✓
Flowmeter (water)	✓	✓	✓	✓	✓
Dispensing area LED light	✓	✓	✓	✓	✓
Coin validator/cashless	-	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
Bookkeeping	-	✓	✓	✓	✓
Monitoring Sanitation / Cleaning Interval	-	✓	✓	✓	✓
Syrup Injection Valve (SIV ³)	✓	✓	✓	✓	✓
Water gallon + pumpset	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL

ALL our models are equipped with the unique and patented mixing system MidMix II.

- 1) FSS = Flood security system: avoids water flood problems due to extra safety valve on water entrance.
- 2) ESI = easy slide in: for fast and easy change of product labels
- 3) SIV - syrup injection valve for perfect mixing result

*Installation of water reduction necessary

SIZE INCL. PACKAGING	JDM SLIM 2 ECO	JDM SLIM 2 STILL	JDM SLIM 2 CO2	JDM SLIM 2 Hot & Cold	JDM SLIM 2 Hot & Ambient
Width	570 mm	570 mm	570 mm	570 mm	570 mm
Height	465 mm	465 mm	465 mm	465 mm	465 mm
Depth	310 mm	310 mm	310 mm	310 mm	310 mm
Weight incl. Packaging	27 kg	27 kg	31 kg	29 kg	15 kg
MACHINE PACKAGE/PALLET					
Europallet 80 x 120 cm	8	8	8	8	8
UK-size pallet 100 x 120 cm	12	12	12	12	12

